

# Jaw Couplings

## Jaw Coupling Data

Coupling No	Nominal Torque (Nm)	Pilot Bore A (mm)	Max Bore A (mm)	Overall Diameter B	Assembled Length L	Hub Width C	Hub Diameter D	Set Screw Position F	Set Screw Size	Complete Weight (kg)
035	-	3	8	16.0	20	7	16.0	3.0	M3	0.06
050	3.51	6	14	27.5	44	16	27.5	6.5	M6	0.10
070	5.77	9	19	35.0	51	19	35.0	9.5	M6	0.25
075	11.90	9	24	44.5	54	21	44.5	8.0	M6	0.45
090	19.20	9	24	54.0	54	21	54.0	8.7	M6	0.55
095	25.80	9	28	54.0	64	25	54.0	11.5	M6	0.65
100	55.40	12	35	65.0	89	35	65.0	12.5	M8	1.60
110	105.00	15	42	84.0	108	43	84.0	20.5	M10	3.00
150	150.00	15	48	96.0	115	45	96.0	22.5	M10	4.90
190	200.00	19	55	115.0	133	54	102.0	22.5	M12	7.00
225	280.00	19	60	127.0	153	64	108.0	25.5	M12	9.00

Angular misalignmet capacity up to 1 deg

Parallel misalignment capacity up to 0.38mm

Mass is for a complete coupling with a pilot bore

Nitrile insert temperature range -40 degC to 100 degC

